



U Protect Slab 4.0 Alu1

U Protect for fire, thermal and acoustic insulation of ventilation and smoke extraction ducts

U Protect Slab 4.0 is part of ISOVER solutions for providing fire resistance in HVAC applications by using high performing ULTIMATE mineral wool. U Protect slabs provide fire resistant, an easy to install, lightweight and efficient thermal and acoustic insulation solution in HVAC for rectangular ventilation and smoke extraction ducts up to EI 120. Installation guidelines must be followed and all ISOVER U Protect components used.



Thermal insulation



Fire resistance



Sound insulation



Fast installation



Sustainable system



Check and download our EPD




U Protect Slab 4.0 Alu1



U Protect for fire, thermal and acoustic insulation of ventilation and smoke extraction ducts

Characteristic	Symbol	Unit	Quantities and measured values							Standard
Application fields	-	-	U Protect Slab 4.0 is part of ISOVER system for providing fire resistance in HVAC applications by using high performing ULTIMATE mineral wool U Protect slabs provides fire resistant, an easy to install, lightweight and efficient thermal and acoustic insulation solution in HVAC for rectangular ventilation and smoke extraction ducts up to EI 120							EN1366-1 EN1366-8
Thermal conductivity	T	[°C]	10	50	100	150	200	300	400	EN 12667
	λ	[W/(m•K)]	0.031	0.035	0.040	0.047	0.054	0.072	0.096	
Maximum service temperature	-	[°C]	< 400 °C (tape and alu-facing 80 °C)							EN 14706
Melting point	-	[°C]	> 1,000 °C							-
Behaviour in fire	-	-	Non-combustible, Euroclass A1							EN 13501-1
Duct orientation			EI15	EI30	EI60	EI190	EI120			
Horizontal thickness	-	mm	30	40	60 (70)	70 (80)	80 (90)	EN 1366-1 EN 1366-8		
Vertical thickness	-	mm	40	50	80	90	100			
Acoustics	α_w	-	Weighted sound absorption coefficient = 0.90							EN 11654
	-	kPa•S/m ³	Specific airflow resistance Afr = 60 (measured without facing)							EN 29053
Water behaviour	-	-	Hydrophobic							EN 12086
Chemical behaviour	-	-	Silicone-free, Sulphide-free							AGI Q 132
CE marking	-	-	MW-EN14303-T4-ST(+)400-MV2							EN 14303
Quality management	-	-	ISOVER is certified according							EN ISO 14001 EN ISO 9001

Delivery form: Standard dimensions / packaging information*				
Width [mm]	Length [mm]	Thickness [mm]	m ² /pack	m ² /pallet
600	1,200	30	9.36	112.3
		40	7.20	86.4
		50	5.76	69.1
		60	4.32	51.8
		70	3.60	43.2
		80	3.60	43.2
		90	2.88	34.6
		100	2.88	34.6

* check availability and delivery details from your local ISOVER supplier

www.isover-technical-insulation.com

The technical information corresponds to our present state of knowledge and experience at the date of printing (see imprint). But no legal guarantee can be given, unless it has been explicitly agreed. The state of experience and knowledge is developing continuously. Please see to it that you always use the latest edition of this information. The described product applications do not take special circumstances in consideration. Please verify whether our products are appropriate for the concrete application. For further information please contact our ISOVER sales offices. We deliver only according to our terms of trade and terms of delivery.

ISOVER
SAINT-GOBAIN