



# EPD

## Isover T-i

Environmental product declaration,  
In accordance with EN 15804+A2 and ISO 14025

# General information

<b>Manufacturer</b>	Saint-Gobain Construction Products CZ a.s., Isover Division, Smrčkova 2485/4, 180 00 Prague 8, Czech Republic
<b>Manufacturer represented</b>	Častolovice, Masarykova 197, 517 50, Czech Republic
<b>About company</b>	Isover offers the widest range of thermal, acoustic and fire insulation in the highest quality on the Czech market, on a global scale it is the most important and largest global manufacturer with operations and production plants all over the world. The complete offer of the Isover brand assortment includes products made of stone and glass wool, expanded polystyrene and accessories for system solutions for insulation of floors, partitions, walls, facades, ceilings, soffits, flat and sloping roofs or pipe distribution.
<b>EPD Programme</b>	The International EPD® System
<b>Registration no</b>	3015-EPD-030064890
<b>Generic PCR review conducted by</b>	EN 15804+A2 Udržitelnost staveb – Environmentální prohlášení o produktu – Základní pravidla pro produktovou kategorii stavebních produktů
<b>Other used standards</b>	EN 16783
<b>Information for the Environmental Product Declaration based on</b>	General report Isover Častolovice, 02/2023
<b>EPD range</b>	„From cradle to gate with option“ (details later in EPD)
<b>Date of publication</b>	26 <sup>th</sup> June 2023
<b>EPD validity</b>	26 <sup>th</sup> June 2028
<b>Complier EPD</b>	Ing. arch. Tomáš Truxa, Isover Division, Saint-Gobain Construction Products CZ a.s.
<b>Verifier EPD</b>	Technický a zkušební ústav stavební Praha, s.p.

Tab. 1 – Information about verifier

The norm EN 15804+A2 prepared CEN serves as a basic PCR	
<p>Independent verification of the environmental declaration and data according to standard ČSN ISO 14025:2010</p> <p><input type="checkbox"/> Internal                      External <input checked="" type="checkbox"/></p>	<p><i>Truxa!</i></p>
<p><b>The third party verifier:</b> Technický a zkušební ústav stavební Praha, s.p. Prosecká 811/76a, Prague 9, 190 00 Czech Republic</p> <p>The certification authority for EPD is accredited ČIA – Český institut pro akreditaci, o.p.s., Osvědčení č. 95/2023.</p>	

# Product description and description of use

This EPD describes the environmental impacts of 1 m<sup>2</sup> of mineral wool product. EPD was created from complete data included all thicknesses of the product. Each thickness influences environmental impacts specifically, their individual impacts were taken into account by the real production and sale rate. Thickness proportions are listed thereafter.

The fibrous structure of mineral wool is very porous and can insulate thanks to the air contained in the individual air cavities. The flexible structure of mineral wool can also absorb sound from the air, from knocking, and thus acts as a comprehensive acoustic insulation. Mineral wool is also non-flammable and its use significantly increases the fire resistance of structures.

Isover T-i boards are intended for thermal, acoustic and fireproof insulation of single-layer flat roofs.



Fig. 1 - Example of Isover T-i application

Tab. 2 - Product parameters for EPD calculation

Parameter	Value
Thickness of product	100 mm (from range 60–140 mm)
Density	112–126 kg/m <sup>3</sup>
Recycled briquette content	35 %
Surfacing	-
Packaging for the distribution and transportation	Stretch film, EPS prisms
Product used for the Installation	-
Implementation loss rate	5 %

Tab. 3 - Technical data / physical characteristics

Parameter	Value
Thermal resistance (100 mm) (EN 12162)	2.70 m <sup>2</sup> ·K·W <sup>-1</sup>
Thermal conductivity coefficient $\lambda_D$ (EN 12667)	0.037 W·m <sup>-1</sup> ·K <sup>-1</sup>
Water vapour transmission (EN 12086)	1 [-]
Compressive strength (EN 826)	40 kPa
Tensile strength (EN 1607)	5 kPa
Reaction to fire class (EN 13 501-1)	A1

More info [www.isover.cz/dokumenty](http://www.isover.cz/dokumenty)

**Tab. 4 – Chemical and hazard information**

Component	C.A.S. number <sup>2)</sup>	Amount weight (%)	Classification and labelling (Regulation (CE) n°1272/2008)
Stone wool <sup>1)</sup>		≥ 95 %	Not classified <sup>3)</sup>
Terpolymerbinder		≤ 5 %	Not classified <sup>3)</sup>

1) Man-made vitreous (silicate) fibres with random orientation with alkaline oxide and alkali earth oxide (Na<sub>2</sub>O+K<sub>2</sub>O+CaO+MgO+BaO) content greater than 18% by weight and fulfilling one of the nota Q conditions.

2) C.A.S.: Chemical Abstract Service.

3) Non classified H351 “suspected of causing cancer”. Stone fibres are not classified carcinogenic according to the note Q of the Directive 97/69/EEC and the regulation n° 1272/2008 (page 335 of the JOCE L353 of December 31, 2008).

More info [www.isover.cz/dokumenty](http://www.isover.cz/dokumenty)

**Most important hazards:** there is no warning notice with this product.

The verifier and program operator make no claims and are not responsible for the legality of the product.

# LCA, input values

Tab. 5 - LCA calculation information

<b>Functional unit (FU)</b>	Providing a thermal insulation on 1 m <sup>2</sup> with a thermal resistance of 2.70 m <sup>2</sup> ·K·W <sup>-1</sup>
<b>System boundaries</b>	„From cradle to gate with option“
<b>Reference service life (RSL)</b>	50 years
<b>Cut-off rules</b>	Boundary conditions for inputs and primary energy at the process level (1%) and information level (5%). Not included are flows resulting from human activities - transport of employees. Plant construction, machinery manufacture and transport system are not included as the associated flows are assumed to be negligible compared to the production of construction materials, relative to the life cycle.
<b>Allocations</b>	Allocation criteria are based on mass
<b>Local conditions</b>	Czech Republic
<b>Assessed period</b>	2021
<b>Comparable</b>	According to EN 15804, EPD of construction products may not be comparable if they do not comply with this standard. According to ISO 21930, EPD might not be comparable if they are from different programmes.
<b>Software</b>	SimaPro 9.4.0.2
<b>Characterization factors</b>	Part of the calculation methods conforming to EN 15804+A2

BUILDING ASSESSMENT INFORMATION										
Information building life cycle information						SUPPLEMENTARY INFORMATION BEYOND THE BUILDING LIFE CYCLE				
A1-A3 PRODUCTS STAGE		A4-A5 CONSTRUCTION PROCESS STAGE		B1-B7 USE STAGE <sup>3)</sup>		C1-C4 END OF LIFE STAGE	D Benefits and loads beyond the system boundary			
A1	Raw material supply	A4	Transport	B1	Use <small>scenario</small>	B5	Reconstruction <small>scenario</small>	C1	Deconstruction / Demolition <small>scenario</small>	REUSE RECOVERY RECYCLING POTENTIAL
A2	Transport	A5	Construction - Installation proces	B2	Maintenance <small>scenario</small>	B6	Operational energy use <small>scenario</small>	C2	Transport <small>scenario</small>	
A3	Manufacturing			B3	Repair <small>scenario</small>	B7	Operational water use <small>scenario</small>	C3	Waste processing <small>scenario</small>	
				B4	Replacement <small>scenario</small>			C4	Disposal <small>scenario</small>	
EPD	Cradle to gate <small>Declared unit</small>	Mandatory						no RSL		
	Cradle to gate with option <small>Declared unit / Functional unit</small>	Mandatory	Inclusion optional <sup>1) 2)</sup>		Inclusion optional <sup>1) 2)</sup>			RSL <sup>1)</sup>	Inclusion optional	
	Cradle to grave <small>Functional unit</small>	Mandatory	Mandatory <sup>1) 2)</sup>		Mandatory <sup>1) 2)</sup>			RSL <sup>2)</sup>	Inclusion optional	

<sup>1)</sup> Inclusion for a declared scenario

<sup>2)</sup> If all scenarios are given

<sup>3)</sup> The effect of the product in stage B1-B7 will be counted at the level of building construction

Fig. 2 - Life cycle phases counted (EN 15804+A2)

# Life cycle stages

## ■ PRODUCT STAGE A1-A3

The product stage of the mineral wool products is subdivided into 3 modules A1, A2 and A3 respectively “Raw material supply”, “transport” and “manufacturing”.

The aggregation of the modules A1, A2 and A3 is a possibility considered by the EN 15804+A2 standard. This rule is applied in this EPD.

### ■ A1 - RAW MATERIAL SUPPLY

This module takes into account the extraction and processing of all raw materials and energy which occur upstream to the studied manufacturing process.

Specifically, the raw material supply covers production binder components and sourcing (quarry) of raw materials for fiber production, e.g. basalt and slag for stone wool. Besides these raw materials, recycled materials (briquettes) are also used as input. See detailed info at the end of this EPD.

### ■ A2 - TRANSPORT TO THE MANUFACTURER

The raw materials are transported to the manufacturing site. In our case, the modelling include: road transportations (average values) of each raw material.

### ■ A3 - MANUFACTURING

This module includes process taking place on the manufacturing site. Specifically, it covers stone wool fabrication including melting and fiberization see process flow diagram and packaging. The production of packaging material is taking into account at this stage.



Fig. 3 - Manufacturing process schema

## ■ CONSTRUCTION PROCESS STAGE A4-A5

Description of the stage: The construction process is divided into 2 modules: transport to the building site A4 and installation A5.

### ■ A4 - TRANSPORT TO THE BUILDING SITE

This module includes transport from the production gate to the building site. Transport is calculated on the basis of a scenario with the parameters described in Table 6.

**Tab. 6 - Scenario for the calculation of stage A4**

Parameter	Value
Fuel type and consumption of vehicle or vehicle type used for transport e.g. long distance truck, boat, etc.	Average truck trailer with a 24t payload, consumption 32 liters for 100 km
Distance to construction site	160 km
Capacity utilisation (including empty returns)	95 % of the capacity in volume 30 % of empty returns
Bulk density of transported products	112-126 kg/m <sup>3</sup>
Volume capacity utilisation factor	1 (by default)

### ■ A5 - INSTALLATION IN THE BUILDING

No additional accessory was taken into account for the implementation phase insulation product.

**Tab. 7 - Scenario for the calculation of stage A5**

Parameter	Value
Wastage of materials on the building site before waste processing, generated by the product's installation (specified by type)	5 %
Output materials (specified by type) as results of waste processing at the building site e.g. of collection for recycling, for energy recovering, disposal (specified by route)	Packaging wastes are 100% collected and modeled as recovered matter
Disposal of unused material	90 % recycling 10 % landfilled
Distance to factory, recycling center, landfill	160 km (recycling) 25 km (landfilled) 60 km (energy use of wooden pallets)
Type of fuel and consumption of the car or type of car used for transport	Average truck trailer with a 7,5-16 t payload, consumption 25 liters for 100 km
Volume capacity utilisation factor	1.3

## ■ USE STAGE B1-B7

The use stage is divided into the following modules:

- **B1 - USE**
- **B2 - MAINTENANCE**
- **B3 - REPAIR**
- **B4 - REPLACEMENT**
- **B5 - REFURBISHMENT**
- **B6 - OPERATIONAL ENERGY USE**
- **B7 - OPERATIONAL WATER USE**

Once installation of the material is completed no further technical operations are required in connection with the thermal insulation during the use of the building until the end of its service life. For this reason these values are not quantified in the EPD. The thermal savings potential shall be calculated at the building level, i.e. outside the EPD product boundaries.

## ■ END-OF-LIFE STAGE C1-C4

This stage includes various end-of-life modules, see below for details.

### ■ **C1 - DECONSTRUCTION, DEMOLITION**

The de-construction and/or dismantling of insulation products take part of the demolition of the entire building. In our case, the environmental impact is assumed to be very small and can be neglected.

### ■ **C2 - TRANSPORT TO WASTE PROCESSING**

A distance of 160 km to the recycling center and 25 km to the landfill is considered.

### ■ **C3 - WASTE PROCESSING FOR REUSE, UTILIZATION AND/OR RECYCLING**

It is considered that 90% of the waste will be reused in the production plant in the form of recycling.

### ■ **C4 - REMOVAL**

In the end-of-life scenario, 10 % landfilling of waste is considered.

**Tab. 8 – Scenario for the calculation of stage C2, C3, C4**

Parameter	Value
Collection process specified by type	11.14 kg (together with mixed construction waste)
Recovery system specified by type	10.26 kg is recycled and reused during the production process as a replacement for the primary raw material
Disposal specified by type	1.14 kg is are landfilled
Assumptions for scenario development (e.g. transportation)	Average truck trailer with a 7,5-16 t payload, consumption 25 liters for 100 km

## ■ REUSE/RECOVERY/RECYCLING POTENTIAL - D

Only the benefits and costs associated with the processing of waste packaging material from the product (recycling packaging foil and energy benefits from pallets).

Note: Savings of primary input materials cannot be precisely determined considering the complexity of production.

# Results LCA

LCA model, aggregation of data and environmental impact are calculated from software SimaPro 9.4.0.2 database of generic data – Ecoinvent 3.8.  
Resume of the LCA results detailed on the following tabs.

**Tab. 9 – Environmental impacts of other thicknesses can be recounted by the design factor (on the material density and thickness base): except for A5**

Thickness (mm)	60	80	100	120	140
Factor	0.66	0.83	1.0	1.18	1.38

**Tab. 10 – Parameters describing the basic environmental impacts**

Indicator - Unit	Product stage	Construction process stage		Use stage	End-of-life stage				Reuse, recovery, recycling
	A1-A3	A4	A5	B1-B7	C1	C2	C3	C4	D
GWP-total Global warming potential kg CO <sub>2</sub> eq.	6.93E+00	3.04E-01	1.98E-02	ND	0	4.87E-01	1.86E-01	6.02E-03	-1.44E-02
GWP-fossil Global warming potential kg CO <sub>2</sub> eq.	6.89E+00	3.03E-01	1.98E-02	ND	0	4.87E-01	1.85E-01	6.00E-03	-1.44E-02
GWP-biogenic Global warming potential kg CO <sub>2</sub> eq.	3.38E-02	2.58E-04	1.80E-05	ND	0	4.45E-04	3.89E-04	5.95E-06	3.08E-05
GWP-luluc Global warming potential from land use and land-use change kg CO <sub>2</sub> eq.	4.53E-03	1.19E-04	9.33E-06	ND	0	2.33E-04	8.76E-05	5.67E-06	-8.88E-06
ODP Stratospheric ozone depletion potential kg CFC 11 eq.	4.96E-07	7.02E-08	4.46E-09	ND	0	1.09E-07	4.83E-08	2.43E-09	-1.01E-09
AP Acidification potential, Cumulative exceedance mol H <sup>+</sup> eq.	3.60E+01	1.23E-03	7.88E-05	ND	0	1.93E-03	1.80E-03	5.65E-05	-4.03E-05
freshwater EP Eutrophication potential, proportion of nutrients entering fresh water kg P eq.	5.84E-03	1.95E-05	1.49E-06	ND	0	3.71E-05	2.00E-05	5.50E-07	-1.88E-06
seawater EP Eutrophication potential, proportion of nutrients entering seawater kg N eq.	1.06E-02	3.71E-04	2.29E-05	ND	0	5.60E-04	7.29E-04	1.96E-05	-1.55E-05
soil EP Eutrophication potential, Cumulative overshoot mol N eq.	1.06E-01	4.05E-03	2.51E-04	ND	0	6.12E-03	7.96E-03	2.15E-04	-1.22E-04
POCP Ground-level ozone formation potential kg NMVOC eq.	3.18E-02	1.24E-03	7.70E-05	ND	0	1.88E-03	2.22E-03	6.25E-05	-4.00E-05
ADP-minerals and metals Raw material depletion potential for non-fossil sources kg Sb eq.	2.62E-05	1.05E-06	9.03E-08	ND	0	2.27E-06	3.05E-07	1.37E-08	-7.13E-08
ADP-fossil fuels Raw material depletion potential for fossil resources MJ, calorific value	1.66E+02	4.58E+00	2.96E-01	ND	0	7.26E+00	3.37E+00	1.68E-01	-1.41E-01
WDP Water scarcity potential (for users), water scarcity weighted by water scarcity m <sup>3</sup> eq. scarcity	2.80E+00	1.37E-02	9.80E-04	ND	0	2.43E-02	7.37E-02	7.55E-03	-2.89E-03

ND = „not declared“

The environmental impact of the product (Module B1-B7) will only become apparent when the product is accounted for within the structure the building.

**Tab. 11 – Additional environmental impacts**

Indicator – Unit	Product stage	Construction process stage		Use stage	End-of-life stage				Reuse, recovery, recycling
	A1–A3	A4	A5	B1–B7	C1	C2	C3	C4	D
PM Potential occurrence of disease due to particulate matter emissions <b>Occurrence of the disease</b>	3.87E-07	3.49E-08	1.47E-09	ND	0	3.59E-08	1.96E-07	1.14E-09	-8.31E-10
IRP Potential effect of human exposure to the isotope U235 <b>kBq U235 eq.</b>	9.99E-01	3.14E-02	1.57E-03	ND	0	3.87E-02	1.95E-02	7.45E-04	-7.58E-04
ETP-fw Potential comparative toxic unit for ecosystems <b>CTUe</b>	2.06E+02	4.77E+00	2.41E-01	ND	0	5.95E+00	2.16E+00	1.06E-01	-1.40E-01
HTP-c Potential comparative toxic unit for humans <b>CTUe</b>	6.97E-08	5.00E-09	2.44E-10	ND	0	6.01E-09	1.55E-09	6.97E-11	-1.53E-10
HTP-nc Potential comparative toxic unit for humans <b>CTUh</b>	5.87E-09	1.54E-10	8.82E-12	ND	0	2.20E-10	9.44E-11	2.69E-12	-1.73E-11
SQP Potential Soil Quality Index <b>dimensionless</b>	4.53E+01	4.20E+00	1.75E-01	ND	0	4.24E+00	3.58E+00	3.52E-01	-1.10E-01

ND = „not declared“

The environmental impact of the product (Module B1-B7) will only become apparent when the product is accounted for within the structure the building.

**Tab. 12 – Resource consumption**

Indicator - Unit	Product stage	Construction process stage		Use stage	End-of-life stage				Reuse, recovery, recycling
	A1-A3	A4	A5	B1-B7	C1	C2	C3	C4	D
PERE Consumption of renewable primary energy, excluding energy sources used as raw materials MJ	1.59E+01	6.46E-02	5.00E-03	ND	0	1.24E-01	6.50E-02	1.43E-03	-6.93E-03
PERM Consumption of renewable primary energy sources used as raw materials MJ	0	0	0	ND	0	0	0	0	0
PERT Total consumption of renewable primary energy sources (primary energy and primary energy sources used as raw materials) MJ	1.59E+01	6.46E-02	5.00E-03	ND	0	1.24E-01	6.50E-02	1.43E-03	-6.93E-03
PENRE Consumption of non-renewable primary energy, excluding energy sources used as raw materials MJ	1.77E+02	4.87E+00	3.14E-01	ND	0	7.71E+00	3.57E+00	1.78E-01	-1.50E-01
PENRM Consumption of non-renewable primary energy sources used as raw materials MJ	0	0	0	ND	0	0	0	0	0
PENRT Total consumption of non-renewable primary energy sources (primary energy and primary energy sources used as raw materials) MJ	1.77E+02	4.87E+00	3.14E-01	ND	0	7.71E+00	3.57E+00	1.78E-01	-1.50E-01
SM Consumption of secondary raw materials kg	2.54E+00	0	0	ND	0	0	0	0	0
RSF Consumption of renewable secondary fuels MJ	0	0	0	ND	0	0	0	0	0
NRSF Consumption of non-renewable secondary fuels MJ	0	0	0	ND	0	0	0	0	0
FW Net potable water consumption m <sup>3</sup>	5.33E-03	0	0	ND	0	0	0	0	0

ND = „not declared“

The environmental impact of the product (Module B1-B7) will only become apparent when the product is accounted for within the structure the building.

**Tab. 13 - Waste category**

Indicator - Unit	Product stage	Construction process stage		Use stage	End-of-life stage				Reuse, recovery, recycling
	A1-A3	A4	A5	B1-B7	C1	C2	C3	C4	D
HWD Hazardous waste disposed of kg	1.73E-03	0	0	ND	0	0	0	0	0
NHWD Other waste disposed of kg	0	0	0	ND	0	0	0	1.14E+00	0
RWD Radioactive waste disposed of kg	0	0	0	ND	0	0	0	0	0

**Tab. 14 - Other output flows**

Indicator - Unit	Product stage	Construction process stage		Use stage	End-of-life stage				Reuse, recovery, recycling
	A1-A3	A4	A5	B1-B7	C1	C2	C3	C4	D
MFR Construction units for reuse kg	0	0	0	ND	0	0	0	0	0
MER Materials for recycling kg	5.90E-03	0	3.86E-02	ND	0	0	1.03E+01	0	0
EEE Materials for energy recovery kg	0	0	0	ND	0	0	0	0	0
EET Exported energy MJ per energy carrier	0	0	0	ND	0	0	0	0	0

**Tab. 15 - the biogenic carbon content of the plant gate (FU = 1 m<sup>2</sup>)**

Indicator - Unit	At the plant gate
Biogenic carbon content of the product kg C	0
Biogenic carbon content in the appropriate packaging kg C	0






ND = „not declared“

The environmental impact of the product (Module B1-B7) will only become apparent when the product is accounted for within the structure the building.

Packaging - without wooden pallet, weight 0 kg per FU, calculation according to EN 16449.

# LCA interpretation

Tab. 16 - The interpretation of results LCA according to SG PCR

	Product stage	Construction process stage		Use stage	End-of-life stage	Environmental impacts of the product	Positive benefits of recycling
		Transport	Installation				
		A1-A3	A4				
<b>Global warming</b>  kg CO <sub>2</sub> equiv/FU						<b>7.93</b> kg CO <sub>2</sub> equiv/FU	-0.01
<b>Non-renewable resources consumption 1)</b>  MJ/FU						<b>181.56</b> MJ/FU	-0.14
<b>Energy consumption 2)</b>  MJ/FU						<b>209.37</b> MJ/FU	-0.16
<b>Water consumption 3)</b>  m <sup>3</sup> /FU						<b>0.01</b> m <sup>3</sup> /FU	0.00
<b>Waste production 4)</b>  kg/FU						<b>1.14</b> kg/FU	0.00

1) This indicator corresponds to the abiotic depletion potential of fossil resources.

2) This indicator corresponds to the total use of primary energy.

3) This indicator corresponds to the use of net fresh water.

4) This indicator expresses to the sum of hazardous, non-hazardous and radioactive waste disposed.

# Environmental positive contribution

## WASTE PROCESSING FOR REUSE, RECOVERY AND/OR RECYCLING

Factory mineral wool waste can be processed into recycled briquettes for mineral wool production. Only internal recycled products (that never leave factory gate) can be used as a production input and it is mentioned only at part A1 - Raw material supply.

Main parts of these briquettes are Milled wet mineral waste, Cement and Bauxit.



Fig. 4 - Briquettes

Second way how to reuse or recycle old mineral wool waste is to mill it and use it as a blown wool for attic floor insulation or for cavity constructions.

This option is now available only for an internal waste recycling (for products, that have never been used in real constructions). That's why this reuse and recycling is not counted also for stages C and D of this EPD.



Fig. 5 - Blown insulation

## RECYCLED CONTENT

The total amount of recycled content in the product Isover T-i according EN ISO 14021 part 7.8 is 76.5 %. The amount of recycled content in the product is divided as follows according to part 7.8.1.1:

Tab. 17 - Recycled content

Parameter	Value
Pre-consumer material	19.5 %
Recycled material	22 %
Recovered material	35 %

The calculation of the recycled content is based on the weight of the product. Data on raw materials and production from 2021 are used in the calculation.

# Additional information

## ENVIRONMENTAL POLICY OF SAINT-GOBAIN

The Saint-Gobain company strives to be a leader in the field of sustainable smelting, therefore it optimizes all processes associated with the supply of environmentally friendly products and promotes the construction of sustainable buildings that consume less energy, resources, produce less waste and emissions in the long term with its integrated solutions.

For all Saint-Gobain products, emphasis is placed on reducing their impact on the environment at all stages of the life cycle and at the same time improving all the useful properties of the products.

The Saint-Gobain group has long-term goals: zero accidents in relation to the environment and constant reduction of environmental impacts (see following Fig. 6). Using mid-term and short-term goals, it then fulfills the long-term goals. The Group places particular emphasis on the following environmental areas: raw materials, waste and recycling, energy, atmospheric emissions, water, biodiversity and accidents with an impact on the environment.

By 2030, Saint-Gobain has set ambitious commitments in the areas of reducing CO<sub>2</sub> emissions, recycling waste, reducing water consumption and product transparency.




Fig. 6 - Long term goals of the group Saint Gobain in the environmental

More informations CSR (Corporate Sustainability Report) on the website [www.saint-gobain.com](http://www.saint-gobain.com)


Production process follows in addition these international standards:  
EN ISO 9001, ISO 14001, OHSAS 18001 a ISO 50001




**THE ELECTRICITY PRODUCTION MODEL CONSIDERED FOR THE MODELLING OF SAINT-GOBAIN PLANT IS:**

401 Electricity (Czech Republic, 2021)

**Tab. 18 – Energy mix for Saint-Gobain production plants**



**Tab. 19 – National energy mix**



\*Residual energy mix. OTE CZ [online]. [cit. 2023-01-13]. Available from [www.ote-cr.cz/cs/statistika/zbytkovy-energeticky-mix](http://www.ote-cr.cz/cs/statistika/zbytkovy-energeticky-mix)

# Source

---

- 1) EN 15804. Sustainability of construction works - Environmental product declarations - Core rules for the product category of construction products. Prague: Úřad pro technickou normalizaci, metrologii a státní zkušebnictví, 2012.
- 2) ČSN ISO 14025. Environmental labels and declarations - Type III environmental declarations - Principles and procedures. Prague: ČESKÝ NORMALIZAČNÍ INSTITUT, 2006
- 3) Environdec PCR (International EPD system). Product group: Multiple UN CPC Codes: INSULATION MATERIALS. version 1.0 (2014:13). Sweden.
- 4) General report Isover Častolovice, 02/2023.

## Do you need advice?

Contact our Business and Technical Support Center:



+420 226 292 221



podpora@saint-gobain.com



Isover Division  
Saint-Gobain Construction Products CZ a.s.  
Smrčkova 2485/4 • 180 00 Prague 8  
Free phone: +420 800 476 837  
[www.isover.cz](http://www.isover.cz)

