

Declaration of Performance

No. CZ0002-009 (eng)

1 Unique identification code of the product-type

108 03

Product/s:

Orstech 65, Orstech 65 NT, Orstech 65 H

TECH Slab MT 3.1, TECH Slab MT 3.1 V1, TECH Slab MT 3.1 Alu2

2 Intended use or uses:

Thermal Insulation of Building Equipment and Industrial Installations (ThIBEI)

3 Manufacturer:

Saint - Gobain Construction Product CZ a.s.
Smrčková 2485/4, 180 00 Prague 8 - Libeň
Czech Republic
IČO: 25029673, DIČ: CZ 25029673

4 Authorised representative:

not relevant

5 Systém/s of AVCP:

System 1
System 3

6 Notified body/ies:

1023

Institut pro testování a certifikaci a.s.

Harmonised standard:

EN 14303:2009 + A1:2013

Essential characteristics	Performance				Abbreviation		Unit		Declared performance/s:	
Reaction to fire	Reaction to fire				RtF		Euroclass		A1	
Acoustic absorption index	Sound absorption				-		-		NPD	
Thermal resistance	Thermal resistance	T °C	50 °C	100 °C	150 °C	200 °C	300 °C	400 °C	500 °C	600 °C
		λ_D (W/m*K)	0,041	0,048	0,058	0,068	0,097	0,134	0,183	0,248
	Thickness				d		mm		40-100	
	Tolerances				T		-		T4	
Water permeability	Water absorption				WS		kg/m ²		WS1	
Water vapour transmission	Water vapour diffusion resistance				S _d		m		NPD	
Rate of release of corrosive substances	Trace amounts of soluble ions and pH value				CL		mg/kg		10	
	Realease of Dangerous Substances				-		-		NPD	
Continous glowing combustion	Continous glowing combustion				-		-		NPD	
Durability of against reaction to fire ageing/degradation	Durability Characteristics				RtF		Euroclass		A1	
Durability of reaction to fire against ageing/degradation and against high temperature	Durability Characteristics				-		-		NPD	
Durability of thermal resistance against ageing/degradation and against high temperature	Maximum Service Temperature				ST(+)		°C		600	
Durability of thermal resistance against heat, weathering, ageing/degradation	Dimensions and tolerances				T		-		T4	
	Dimensional stability, or				DS(TH)		-		NPD	
	Maximum Service Temperature				ST(+)		°C		600	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued by the Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Jiří Šulák
Name
Plant director
Function


Signature

1.5.2025
Date
Častolovice
Place


SAINT-GOBAIN
e-mail: info@isover.cz
www.isover.cz