

## **→**

### Protect BSK glue

### U Protect for fire, thermal and acoustic insulation of ventilation and smoke extraction ducts

U Protect system is designed to provide fire resistant, an easy to install, lightweight and efficient thermal and acoustic insulation solution in HVAC for circular and rectangular ventilation and smoke extraction ducts up to EI 120. Protect BSK is part of ISOVER U Protect fire resistant solution. Installation guidelines must be followed and all ISOVER U Protect components used.



Fire resistance



**Fast installation** 



**Indoor air quality** 





### Protect BSK glue



# U Protect for fire, thermal and acoustic insulation of ventilation and smoke extraction ducts

Characteristic	Symbol	Unit	Quantities and measured values	Standard
Application fields	-	-	Protect BSK glue is part of ISOVER U Protect fire resistant solution up to EI120 for ventilation and smoke extraction ducts	EN 1366-1 EN 1366-8
Material	-	-	Inorganic Protect BSK glue	-
Behaviour in fire	-	-	Non combustible	DIN 4102-4
Processing temperature	Т	°C	+ 5 to + 30 °C	-
Packaging	-	-	8 kg PP-bucket with lid 310 ml cartridges (12 units in box)	-
Storage condition	-	-	T > 0 °C to + 35 °C storage time 12 months	-
Chemical behaviour	-	-	Inorganic, Alkaline solution Free of Volatile Organic compounds	-
Instructions of use	-	-	Before use, material must be stirred well Can be diluted up to 10 % or water Application by brush, roller or spatula Surface must be clean and dry and free of dust and grease Hardened after ~12 hours under normal conditions (20 °C, RH 50 %)	-
Classification	-	-	Protect BSK contains no particular hazardous substances for human or environment so no classification according to CLP (EC) 1272/2008 or classification according to REACH (EC) 1907/2006 needed	-

#### www.isover-technical-insulation.com

The technical information corresponds to our present state of knowledge and experience at the date of printing (see imprint). But no legal guarantee can be given, unless it has been explicitly agreed. The state of experience and knowledge is developing continuously. Please see to it that you always use the latest edition of this information. The described product applications do not take special circumstances in consideration. Please verify whether our products are appropriate for the concrete application. For further information please contact our ISOVER sales offices. We deliver only according to our terms of trade and terms of delivery.

