



# Isover Vario® Stretch

Universal adhesive tape for indoor and outdoor use

## TECHNICAL SPECIFICATION

A highly flexible adhesive tape that can be used to quickly and easily seal interior and exterior penetrations through an airtight vapour barrier layer with a variable equivalent diffusion thickness.



## USES

For airtight sealing of penetrations and passages. Flexible tape, saves up to 50% installation time compared to standard tapes. Suitable for ventilation flexi-pipes and penetrations, cable bundles or beams. The two-part protective film on the back of the tape makes it even easier to use and seals flexibly. The two-part protective film on the back of the adhesive tape makes it even easier to use. Ideal for use with Isover Vario® KM Duplex UV and Isover Vario® XtraSafe vapour barriers.

## APPLICATION

Remove the protective film and simply adhere Isover Vario® Stretch to the substrate. The substrate must be stable, dust-free, non-greasy and dry. Carry out a test bonding. Press the adhesive tape firmly with a squeegee onto the substrate and penetrate without damaging it. Follow the instructions at [www.isover.cz](http://www.isover.cz) for installation.

## PACKAGING, TRANSPORT, WAREHOUSING

Protect against UV rays in a dry and dust-free environment. The application surface should be free of grease and dust. Store at a temperature of +5 to +25 °C.

## DIMENSIONS AND PACKAGING

Width [mm]	Roll length [m]	Weight [kg]
80	10	2.5

## TECHNICAL PARAMETERS

Features	Parameters and measured values
Temperature resistance	-40 to +80 °C
Application temperature	+5 to +40 °C
Storage temperature	+5 to +25 °C
Chemical composition	Free of solvents, isocyanates, PVC, heavy metals and halogens.
Resistance to wood preservatives	The adhesive and sealing tape is resistant to water-soluble and oil-based wood preservatives.
UV resistance	12 months
Suitable substrates	PE, PA, PU, PP and aluminium foils, kraft paper, metals, hard wood-based materials (OSB, chipboard, etc.). The substrate may be slightly damp (slight residual moisture from plaster) but must be free of dust and grease.

## RELATED DOCUMENTS

- Declaration of Performance

1/8/2025 The information provided herein is valid at the time of publication. The manufacturer reserves the right to change the data.