

# Declaration of Performance

No. **CZ0001-013**

1 Unique identification code of the product-type

S01 03

Product/s:

**Isover T-i**

2 Intended use or uses:

Thermal insulation for buildings (ThIB)

3 Manufacturer:

**Saint - Gobain Construction Product CZ a.s.**  
**Smrčkova 2485/4, 180 00 Prague 8 - Libeň**  
**Czech Republic**  
**IČO: 25029673, DIČ: CZ 25029673**

4 Authorised representative:

not relevant

5 Systém/s of AVCP:

System 1  
System 3

6 Notified body/ies:

**1023**

Institut pro testování a certifikaci a.s.

Harmonised standard:

EN 13162:2012+A1:2015

Essential characteristics	Performance		Unit	Declared performance
Reaction to fire	Reaction to fire	RtF	Euroclass	A1
Release of Dangerous Substances	Release of Dangerous Substances	-	-	NPD
Acoustic absorption index	Sound absorption	-	-	NPD
Impact Noise Transmission Index	Dynamic stiffness	s'	MN/m³	NPD
	Thickness	d <sub>i</sub>	mm	NPD
	Compressibility	c	mm	NPD
	Air flow resistivity	AF <sub>r</sub>	kPa.s/m²	NPD
Direct airborne sound insulation index	Air flow resistivity	AF <sub>r</sub>	kPa.s/m²	NPD
Continuous glowing combustion	Continuous glowing combustion	-	-	NPD
Thermal Resistance	Thermal Resistance	R <sub>D</sub>	m² K/W	a)
	Thermal Conductivity	λ <sub>D</sub>	W/m K	0,037
	Thickness	d <sub>N</sub>	mm	30-160
	Thickness Class	T	Class	T5
Water Permeability	Short term Water absorption	W <sub>p</sub>	kg/m²	1
	Long term water absorption	W <sub>lp</sub>	kg/m²	3
Water vapour permeability	Water vapour transmission	MU	-	1
Compressive strength	Compressive stress or compressive strength	CS	kPa	40
	Point Load	F <sub>p</sub>	N	NPD
Durability of reaction to fire against heat, weathering, ageing/degradation	Reaction to fire	RtF	Euroclass	A1
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal Resistance	R	m² K/W	a)
	Thermal Conductivity	λ	W/m K	0,037
	Durability Characteristics	d	mm	NPD
Tensile/Flexural strength	Tensile Strength perpendicular to faces	TR	kPa	5
Durability of compressive strength against heat, weathering, ageing/degradation	Compressive creep	Xct, Xt	mm	NPD

a) The parameter R is valid for the thickness of the product, range of thickness and thermal resistance - see product data sheet on the web [www.isoover.cz](http://www.isoover.cz)

Table 2

Thickness [mm]	Length × width [mm]	Transport packaging [m³]	Volume per package [m³]	Declared thermal resistance R <sub>D</sub> [m² K/W]
30	2 000 × 1 200	3.024	100.8	0.80
40	2 000 × 1 200	2.880	72.0	1.05
50	2 000 × 1 200	3.000	60.0	1.35
60	2 000 × 1 200	3.024	50.4	1.60
70	2 000 × 1 200	3.024	43.2	1.85
80	2 000 × 1 200	3.070	38.4	2.15
100	2 000 × 1 200	3.120	31.2	2.70
120	2 000 × 1 200	3.168	26.4	3.20
140	2 000 × 1 200	3.024	21.6	3.75
160	2 000 × 1 200	3.072	19.2	4.30

Specification code:

MW-EN 13162-T5-CS(10)40-TR5-WS-WL(P)-MU1

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued by the Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Jiří Šulák  
Name

Plant director  
Function



Signature

Častolovice  
Place

1.7.2024  
Date



e-mail: [info@isoover.cz](mailto:info@isoover.cz), [www.isoover.cz](http://www.isoover.cz)