

Declaration of Performance

No. CZ0002-010 (eng)

1	Unique identification code of the product-type	I01 03
	Product/s:	Orstech DP 65, Orstech DP 65 ALU TECH Wired Mat MT 3.1, TECH Wired Mat MT 3.1 Alu1
2	Intended use or uses:	Thermal insulation of Building Equipment and Industrial Installations
3	Manufacturer:	Saint - Gobain Construction Product CZ a.s. Smrčkova 2485/4, 180 00 Prague 8 – Libeň Czech Republic IČO: 25029673, DIČ: CZ 25029673
4	Authorised representative:	not relevant
5	Systém/s of AVCP:	System 1 System 3
6	Notified body/ies:	1390 Centrum stavebního inženýrství a.s. Praha
	Harmonised standard:	EN 14 303:2009 + A1:2013

Essential characteristics	Performance	Abbreviation	Unit	Declared performance/s:						
Reaction to fire	Reaction to fire	RtF	Euroclass	A1						
Acoustic absorption index	Sound absorption	-	-	NPD						
Thermal resistance	Thermal resistance	T °C	50 °C	100 °C	150 °C	200 °C	300 °C	400 °C	500 °C	600 °C
		λ_D (W/m K)	0,041	0,048	0,058	0,068	0,097	0,134	0,183	0,248
	Thickness	d	mm	40-100						
	Tolerances	T		T2						
Water permeability	Water absorption	WS	kg/m ²	WS1						
Water vapour transmission	Water vapour diffusion resistance	S _d	m	NPD						
Rate of release of corrosive substances	Trace amounts of soluble ions and pH value	CL	mg/kg	10						
	Realease of Dangerous Substances	-	-	NPD						
Continous glowing combustion	Continous glowing combustion	-	-	NPD						
Durability of against reaction to fire ageing/degradation	Durability Characteristics	RtF	Euroclass	A1						
Durability of reaction to fire against ageing/degradation and against high temperature	Durability Characteristics	-	-	NPD						
Durability of thermal resistance against ageing/degradation and against high	Maximum Service Temperature	ST(+)	°C	560						
Durability of thermal resistance against heat, weathering, ageing/degradation	Dimensions and tolerances	T	-	T2						
	Dimensional stability, or	DS(TH)	-	NPD						
	Maximum Service Temperature	ST(+)	°C	560						

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued by the Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Jiří Šulák
Name
Plant director
Function



1.7.2017
Date
Častolovice
Place

ISOVER
SAINT-GOBAIN
e-mail: info@isover.cz
www.isover.cz