

Declaration of Performance

No. CZ0001-006

1	Unique identification code of the product-type	S01 01
	Product/s:	Isover FASSIL Isover FASSIL NT
2	Intended use or uses:	Thermal insulation for buildings
3	Manufacturer:	Saint - Gobain Construction Product CZ a.s. Počernická 272/96; 108 03 Prague 10 Czech Republic IČO: 25029673, DIČ: CZ 25029673
4	Authorised representative:	not relevant
5	Systém/s of AVCP:	System 1 System 3
6	Notified body/ies:	1390 Centrum stavebního inženýrství a.s. Praha
	Harmonised standard:	EN 13 162: 2012

Essential characteristics	Performance	Abbreviation	Unit	Declared performance
Reaction to fire	Reaction to fire	RtF	Euroclass	A1
Realease of Dangerous Substances	Realease of Dangerous Substances	-	-	NPD
Acoustic absorption index	Sound absorption	-	-	b)
Impact Noise Transmission Index	Dynamic stiffness	s'	MN/m ³	NPD
	Thickness	d _L	mm	NPD
	Compressibility	c	mm	NPD
	Air flow resistivity	AF _r	kPa.s/m ²	≥ 14,5
Direct airborne sound insulation index	Air flow resistivity	AF _r	kPa.s/m ²	≥ 14,5
Continous glowing combustion	Continous glowing combustion	-	-	NPD
Thermal Resistance	Thermal Resistance	R _D	m ² K/W	a)
	Thermal Conductivity	λ _D	W/m K	0,035
	Thickness	d _N	mm	50-200
	Thickness Class	T	Class	T4
Water Permeability	Short term Water absorption	W _p	kg/m ²	NPD
	Long term water absorption	W _{lp}	kg/m ²	NPD
Water vapour permeability	Water vapour transmission	μ	-	1
Compressive strength	Compressive stress or compressive strength	CS	kPa	NPD
	Point Load	F _p	N	NPD
Durability of reaction to fire against heat, weathering, ageing/degradation	Reaction to fire	RtF	Euroclass	A1
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal Resistance	R	m ² K/W	a)
	Thermal Conductivity	λ	W/m K	0,035
	Durability Characteristics	d	mm	NPD
Tensile/Flexural strength	Tensile Strength perpendicular to faces	TR	kPa	NPD
Durability of compressive strength against heat, weathering, ageing/degradation	Compressive creep	Xct, Xt	mm	NPD

a) The parameter R is valid for the thickness of the product, range of thickness and thermal resistance - see product data sheet on the web www.isover.cz

b) Sound absorption parameter is valid for the product thickness, thickness range and sound absorption values - see product data sheet on the website www.isover.cz

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued by the Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. Declaration of cut products Isover TRV is derived from the declared parameters of this product.

Jiří Šulák
Name

Plant director

Function



Signature

Častolovice
Place

01.12.2014

Date

ISOVER
SAINT-GOBAIN

e-mail: info@isover.cz, www.isover.cz