

Declaration of Performance

No. **CZ0001-013**

1 Unique identification code of the product-type S01 03

Product/s:

Isover T-i

2 Intended use or uses: Thermal insulation for buildings (ThIB)

3 Manufacturer: **Saint - Gobain Construction Product CZ a.s.**
Smrčková 2485/4, 180 00 Prague 8 - Libeň
Czech Republic
IČO: 25029673, DIČ: CZ 25029673

4 Authorised representative: not relevant

5 Systém/s of AVCP: System 1
System 3

6 Notified body/ies: **1023** Institut pro testování a certifikaci a.s.

Harmonised standard: EN 13162:2012+A1:2015

Essential characteristics	Performance		Unit	Declared performance
Reaction to fire	Reaction to fire	RtF	Euroclass	A1
Realease of Dangerous Substances	Realease of Dangerous Substances	-	-	NPD
Acoustic absorption index	Sound absorption	-	-	NPD
	Dynamic stiffness	s'	MN/m ²	NPD
Impact Noise Transmission Index	Thickness	d _i	mm	NPD
	Compressibility	c	mm	NPD
	Air flow resistivity	AF _r	kPa.s/m ²	NPD
	Direct airborne sound insulation index	Air flow resistivity	AF _r	kPa.s/m ²
Continous glowing combustion	Continous glowing combustion	-	-	NPD
Thermal Resistance	Thermal Resistance	R _D	m ² K/W	a)
	Thermal Conductivity	λ _D	W/m K	0,037
	Thickness	d _N	mm	30-160
	Thickness Class	T	Class	T5
Water Permeability	Short term Water absorption	W _p	kg/m ²	1
	Long term water absorption	W _{lp}	kg/m ²	3
Water vapour permeability	Water vapour transmission	MU	-	1
Compressive strength	Compressive stress or compressive strength	CS	kPa	40
	Point Load	F _p	N	NPD
Durability of reaction to fire against heat, weathering, ageing/degradation	Reaction to fire	RtF	Euroclass	A1
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal Resistance	R	m ² K/W	a)
	Thermal Conductivity	λ	W/m K	0,037
	Durability Characteristics	d	mm	NPD
Tensile/Flexural strength	Tensile Strength perpendicular to faces	TR	kPa	5
Durability of compressive strength against heat, weathering, ageing/degradation	Compressive creep	Xct, Xt	mm	NPD

a) The parameter R is valid for the thickness of the product, range of thickness and thermal resistance - see product data sheet on the web www.isover.cz

Table 2

Thickness [mm]	Length × width [mm]	Transport packaging [m ³]	Volume per package [m ³]	Declared thermal resistance R _D [m ² ·K·W ⁻¹]
30	2 000 × 1 200	3,024	100,8	0,80
40	2 000 × 1 200	2,880	72,0	1,05
50	2 000 × 1 200	2,880	57,6	1,35
60	2 000 × 1 200	2,880	48,0	1,60
70	2 000 × 1 200	3,024	43,2	1,85
80	2 000 × 1 200	3,070	38,4	2,15
100	2 000 × 1 200	3,120	31,2	2,70
120	2 000 × 1 200	2,880	24,0	3,20
140	2 000 × 1 200	3,024	19,2	3,75
160	2 000 × 1 200	3,024	19,2	4,30

Specification code:

MW-EN 13162-T5-CS(10)40-TR5-WS-WL(P)-MU1

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued by the Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Jiří Šulák
Name

Plant director
Function



Signature

Častolovice
Place

7.6.2023
Date

ISOVER
SAINT-GOBAIN

e-mail: info@isover.cz, www.isover.cz