

Declaration of Performance

No. CZ0001-012

1 Unique identification code of the product-type

S01 03

Product/s:

Isover P

2 Intended use or uses:

Thermal insulation for buildings (ThIB)

3 Manufacturer:

Saint - Gobain Construction Product CZ a.s.
Smrčkova 2485/4, 180 00 Prague 8 – Libeň
Czech Republic
IČO: 25029673, DIČ: CZ 25029673

4 Authorised representative:

not relevant

5 Systém/s of AVCP:

System 1
System 3

6 Notified body/ies:

1023

Institut pro testování a certifikaci a.s.

Harmonised standard:

EN 13162:2012+A1:2015

Essential characteristics	Performance		Unit	Declared performance
Reaction to fire	Reaction to fire	RtF	Euroclass	A1
Realease of Dangerous Substances	Realease of Dangerous Substances	-	-	NPD
Acoustic absorption index	Sound absorption	-	-	NPD
Impact Noise Transmission Index	Dynamic stiffness	s'	MN/m ³	NPD
	Thickness	d_t	mm	NPD
	Compressibility	c	mm	NPD
	Air flow resistivity	AF_r	kPa.s/m ²	NPD
Direct airborne sound insulation index	Air flow resistivity	AF_r	kPa.s/m ²	NPD
Continous glowing combustion	Continous glowing combustion	-	-	NPD
Thermal Resistance	Thermal Resistance	R_D	m ² K/W	a)
	Thermal Conductivity	λ_D	W/m K	0,036
	Thickness	d_N	mm	20-160
	Thickness Class	T	Class	T4
Water Permeability	Short term Water absorption	W_p	kg/m ²	1
	Long term water absorption	W_{lp}	kg/m ²	3
Water vapour permeability	Water vapour transmission	MU	-	1
Compressive strength	Compressive stress or compressive strength	CS	kPa	20
	Point Load	F_p	N	NPD
Durability of reaction to fire against heat, weathering, ageing/degradation	Reaction to fire	RtF	Euroclass	A1
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal Resistance	R	m ² K/W	a)
	Thermal Conductivity	λ	W/m K	0,036
	Durability Characteristics	d	mm	NPD
Tensile/Flexural strength	Tensile Strength perpendicular to faces	TR	kPa	1
Durability of compressive strength against heat, weathering, ageing/degradation	Compressive creep	Xct, Xt	mm	NPD

a) The parameter R is valid for the thickness of the product, range of thickness and thermal resistance - see product data sheet on the web www.isover.cz

Table 2

Thickness [mm]	Length x width [mm]	Transport packaging [m ³]	Volume per package [m ³]	Declared thermal resistance R_D [m ² ·K·W ⁻¹]
20	1000 x 1250	1.500	75.0	0.55
30	1000 x 1250	1.575	52.5	0.80
60	2 000 x 1 200	3.024	50.4	1.65
80	2 000 x 1 200	2.880	36.0	2.20
100	2 000 x 1 200	3.120	31.2	2.75
120	2 000 x 1 200	2.880	24.0	3.30
140	2 000 x 1 200	2.688	19.2	3.85
160	2 000 x 1 200	3.072	19.2	4.40

Specification code:

MW-EN 13162-T4-DS(70,-)-CS(10)20-TR1-WS-WL(P)-MU1

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued by the Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. Declaration of cut products Isover SD, Isover DK, Isover AK is derived from the declared parameters of this product.

Jiří Šulák

Name

Plant director

Function



Signature

Častolovice

Place

15.4.2024

Date

ISOVER
SAINT-GOBAIN

e-mail: info@isover.cz, www.isover.cz