

1	Unique identification code of the product-type	S01 01
	Product/s:	Isover MAXIL / MAXIL NT
2	Intended use or uses:	Thermal insulation for buildings (ThIB)
3	Manufacturer:	Saint - Gobain Construction Product CZ a.s. Smrčková 2485/4, 180 00 Prague 8 – Libeň Czech Republic IČO: 25029673, DIČ: CZ 25029673
4	Authorised representative:	not relevant
5	Systém/s of AVCP:	System 1 System 3
6	Notified body/ies:	1390 Centrum stavebního inženýrství a.s. Praha
	Harmonised standard:	EN 13162:2012+A1:2015

Essential characteristics	Performance		Unit	Declared performance
Reaction to fire	Reaction to fire	RtF	Euroclass	A1
Release of Dangerous Substances	Release of Dangerous Substances	-	-	NPD
Acoustic absorption index	Sound absorption	-	-	NPD
Impact Noise Transmission Index	Dynamic stiffness	s'	MN/m ³	NPD
	Thickness	d _L	mm	NPD
	Compressibility	c	mm	NPD
	Air flow resistivity	AF _r	kPa.s/m ²	NPD
Direct airborne sound insulation index	Air flow resistivity	AF _r	kPa.s/m ²	NPD
Continous glowing combustion	Continous glowing combustion	-	-	NPD
Thermal Resistance	Thermal Resistance	R _D	m ² K/W	a)
	Thermal Conductivity	λ _D	W/m K	0,034
	Thickness	d _N	mm	30-100
	Thickness Class	T	Class	T4
Water Permeability	Short term Water absorption	W _p	kg/m ²	NPD
	Long term water absorption	W _{lp}	kg/m ²	NPD
Water vapour permeability	Water vapour transmission	MU	-	1
Compressive strength	Compressive stress or compressive strength	CS	kPa	NPD
	Point Load	F _p	N	NPD
Durability of reaction to fire against heat, weathering, ageing/degradation	Reaction to fire	RtF	Euroclass	A1
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal Resistance	R	m ² K/W	a)
	Thermal Conductivity	λ	W/m K	0,034
	Durability Characteristics	d	mm	NPD
Tensile/Flexural strength	Tensile Strength perpendicular to faces	TR	kPa	NPD
Durability of compressive strength against heat, weathering, ageing/degradation	Compressive creep	Xct, Xt	mm	NPD

a) The parameter R is valid for the thickness of the product, range of thickness and thermal resistance - see Table 2 or product data sheet on the web www.isover.cz

Table 2

Thickness [mm]	30*	40*	50*	60*	80*	100*
Length x width [mm]	1200 x 600					
Volume per package [ks]	14	10	8	7	5	4
Volume per package [m ³]	10.08	7.20	5.76	5.04	3.60	2.88
Quantity per palette [m ²]	0.32	0.29	0.29	0.30	0.29	0.29
Quantity per palette [m ²]	120.96	86.40	69.12	60.48	43.20	34.56
Declared thermal resistance R _p [m ² ·K·W ⁻¹]	0.85	1.15	1.45	1.75	2.35	2.90

* It is necessary to consult with the producer for the terms of delivery.


Specification code:

MW-EN 13162-T4-MU1

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued by the Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Jiří Šulák
Name

Plant director
Function



Signature

Častolovice
Place

22.10.2019
Date

ISOVER
SAINT-GOBAIN

e-mail: info@isover.cz, www.isover.cz