

Declaration of Performance

DoP CZ0001-023

1 Unique identification code of the product-type: S01 04

Product/s:

Isover NF 333
Isover NF 333V
Fasoterm

2 Intended use or uses: Thermal insulation for buildings

3 Manufacturer:

Saint - Gobain Construction Product CZ a.s.
Smrčková 2485/4, 180 00 Prague 8 – Libeň
Czech Republic
IČO: 25029673, DIČ: CZ 25029673

4 Authorised representative:

not relevant

5 System/s of AVCP:

System 1
System 3

6 Notified body/ies:

1390

Centrum stavebního inženýrství a.s. Praha

Harmonised standard:

EN 13 162: 2012+A1:2015

Essential characteristics	Performance	Abreviation	Unit	Declared performance
Reaction to fire	Reaction to fire	RtF	Euroclass	A1
Realease of Dangerous Substances	Realease of Dangerous Substances	-	-	NPD
Acoustic absorption index	Sound absorption	-	-	NPD
Impact Noise Transmission Index	Dynamic stiffness	SDi	MN/m ²	NPD
	Thickness	d _L	mm	20-300 50-200 (NF 333 V)
	Compressibility	c	mm	NPD
	Air flow resistivity	AF _r	kPa.s/m ²	NPD
Direct airborne sound insulation index	Air flow resistivity	AF _r	kPa.s/m ²	NPD
Continous glowing combustion	Continous glowing combustion	-	-	NPD
Thermal Resistance	Thermal Resistance	R _D	m ² K/W	a)
	Thermal Conductivity	λ _D	W/m K	0,041
	Thickness	d _N	mm	NDP
	Thickness Class	Ti	Class	T5
Water Permeability	Short term Water absorption	W _p	kg/m ²	1
	Long term water absorption	W _{lp}	kg/m ²	3
Water vapour permeability	Water vapour transmission	μ	-	1
Compressive strength	Compressive stress or compressive strength	CS(Y)	kPa	NPD
	Point Load	F _p	N	NPD
Durability of reaction to fire against heat, weathering, ageing/degradation	Reaction to fire	RtF	Euroclass	A1
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal Resistance	R _D	m ² K/W	a)
	Thermal Conductivity	λ _D	W/m K	0,041
	Durability Characteristics	d	mm	NPD
Tensile/Flexural strength	Tensile Strength perpendicular to faces	TR	kPa	80
Durability of compressive strength against heat, weathering, ageing/degradation	Compressive creep	Xct, Xt	mm	NPD

a) The parameter R is dependent on the thickness of the final sandwich panel.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Jiří Šulák
Name
Plant director
Function



Častolovice
Place
1.7.2017
Date

ISOVER
SAINT-GOBAIN

e-mail: info@isover.cz, www.isover.cz