

Isover VARIO® XtraTape Isover VARIO® XtraFix Isover VARIO® XtraFit List of accessories

TECHNICAL SPECIFICATION

The system of VARIO® accessories was developed specifically for bonding joints and details of the vapour barriers Isover VARIO® XtraSafe.

APPLICATION

Easy formability and adaptability in details of Isover VARIO® XtraTape is ensured by an extra wide adhesive tape with extremely high adhesive strength. Developed specifically for safe airtight bonding of VARIO® vapour barrier overlaps. It can be used in corners, joints and roof passages and for attaching the vapour barrier to rafters, purlins, skylights, etc. Processing temperature $\geq -10^{\circ}\text{C}$ (Temperature resistance -30°C to $+100^{\circ}\text{C}$.)

Isover VARIO® XtraFix is a hook-and-loop tape is especially adjusted to the variable smart vapor retarder Isover VARIO® XtraSafe and suitable for the repositionable installation of this vapor barrier sheet. Processing temperature $\geq -10^{\circ}\text{C}$. (Temperature resistance -30°C to $+100^{\circ}\text{C}$.)

Isover VARIO® XtraFit is a two-part selling material without solvents, resistant to separation, suitable for realization of all airtight joints to various construction parts, e.g. gable walls, purlins, windows, doors. With no pressure lath required, it is applied in 6-8 mm layer to ensure permanent airtight connection of the vapour barrier to peripheral masonry constructions. It is packed in a convenient cartridge or in a bigger, nearly wasteless package (roll in a foil). Processing temperature $\geq +5^{\circ}\text{C}$. (Temperature resistance -40°C to $+100^{\circ}\text{C}$.)

PACKAGING, TRANSPORT, WAREHOUSING

Accessories VARIO® has package in a boxes with a couple peaces. By transporting may not be any mechanical damage of product, stocking at dry place.

BENEFITS

- adaptable protection against air humidity and condensate
- variably diffusion permeable - water vapour permeability
- environmentally friendly and hygienic
- together with sealing and adhesive tapes creates a water vapour barrier system
- easy formability and adaptability in details



DIMENSIONS AND PACKAGING

	Isover VARIO® XtraTape	Isover VARIO® XtraFix	Isover VARIO® XtraFit
Dimensions [mm]	20 000 x 60	25 000 x 10	-
Packaging	20 m	25 m	310 ml